



GENERAL DESCRIPTION

3-ply Surgical Mask, ASTM Level 2

- ❖ Bacterial Filtration Efficient(BFE) > 98%
- ❖ Particulates Filtration Efficient(PFE) > 98%
- ❖ Breathing Resistance < 60 mmH₂O/cm²
- ❖ Synthetic Blood Penetration Resistance @ 120mmHg
- ❖ Product Color: Blue
- ❖ Sterilization: Non-sterile
- ❖ Class 1 -normal flammability
- ❖ Package: 50pcs/box,40boxes/carton

MATERIAL COMPOSITION

- ❖ Outer Layer - Spunbonded polypropylene blue 30gsm±2gsm
- ❖ Filter Layer - Melt-blown filter paper white 30gsm ± 2gsm
- ❖ Inner Layer - Spunbonded polypropylene white 25gsm ± 2gsm
- ❖ Ear Loop - Elastic spandex, latex free
- ❖ Nose Strip - Polyethylene coated double galvanized wire
- ❖ This mask contains no components made from natural rubber latex
- ❖ Approximate weight of product: 3.0 grams / 0.1 oz



DIMENSION

- ❖ Size - 17.5X9.5cm±0.3cm
- ❖ Ear Loop - 16.0cm±0.5cm
- ❖ Nose Strip - 11.0cm±0.5cm
- ❖ Inner Bag - PE (N/A)
- ❖ Inner Box - White Cardboard (19x10x8.0cm)
- ❖ Outer Case - 5ply Corrugated Paperboard (52x40x34cm)

INTENDED USAGE

- ❖ Intended use surgical masks are intended to be worn by the general public or healthcare personnel and cover the user's nose and mouth.
- ❖ The mask provide a physical barrier that blocks pollutants in the nose and mouth and reduces the risk of spreading viruses and breathing airborne particles.

TIME USE LIMITATION

- ❖ Shelf Life: 3 years.
- ❖ Replace the mask when it becomes dirty, damaged, or difficult to breathe through.
- ❖ Storage and transport: keep in a ventilated and dry room, prevent heavyweight, direct sunlight, rain, and snow immersion.

For More Information:

86.512.6262.1607

sales@wellmien.com

www.wellmien.com

Wellmien