

# MEDICAL SUPPLY

### **Technical Specification Sheet**

# **GENERAL DESCRIPTION**

#### 3-ply Medical Masks, TYPE II, EN14683:2019

- Bacterial Filtration Efficient(BFE) > 99%
- Particulates Filtration Efficient(PFE) > 98%
- Breathing Resistance < 40 mmH20/cm2</li>
- Synthetic Blood Penetration Resistance N/A

### **MATERIAL COMPOSITION**

- Outer Layer Spunbonded polypropylene -Blue 25gsm±2gsm
- Filter Layer Melt-blown filter paper
  -White 25gsm ± 2gsm
- Inner Layer Spunbonded polypropylene -White 25gsm ± 2gsm
- Ear Loop Elastic spandex, latex free
- Nose Strip Polyethylene coated double galvanized wire
- This mask contains no components made from natural rubber latex
- Approximate weight of product: 2.6 grams

### DIMENSION

- ✤ Size 17.5X9.5cm±0.3cm
- ✤ Ear Loop 16.0cm±0.5cm
- ✤ Nose Strip 11.0cm±0.5cm

- Product Color: Blue
- Sterilization: Non-sterile
- Class 1 -normal flammability
- Package: 50pcs/box,40boxes/carton



- Inner Bag PE (N/A)
- Inner Box White Cardboard (19x10x7cm)
- Outer Case 5ply Corrugated Paperboard (52x40x30cm)

# **INTENDED USAGE**

- Intended use medical masks are intended to be worn by the general public or healthcare personnel and cover the user's nose and mouth.
- The mask provide a physical barrier that blocks pollutants in the nose and mouth and reduces the risk of spreading viruses and breathing airborne particles.

# TIME USE LIMITATION

- Shelf Life: 3 years.
- Replace the mask when it becomes dirty, damaged, or difficult to breathe through.
- Storage and transport: keep in a ventilated and dry room, prevent heavyweight, direct sunlight, rain, and snow immersion.

#### For More Information:

86.512.6262.1607 sales@wellmien.com www.wellmien.com

